falmec

8034122369778

Falmec Lab

Motor rotatable in 4 directions

Įtrauktas nuotolinio valdymo pultas
Dialogue system

Dynamic LED Light
Dimmable led lighting
Strip LED 2x20 W - 2700 K / 5600 K

100 cm

150 cm

150 cm

170 W

220-240V 50-60Hz

Shuko

800 m^3/h

605 m^3/h I.E.C.61591

57 dB (A)re1pW I.E.C. 60704-2-13

A

30.1 kg

24.2 kg

0.29 m3

L 1330 x H 307 x P 725 mm







KACL.939#BF	Ceiling re-circulation filtering kit (only for Slim Motor)
KACL.928	Replacement Carbon.Zeo filter for horizontal outlet
KACL.953#BF	Carbon.Zeo vertical outlet ceiling filter unit kit
KACL.931	Filter replacement Carbon.Zeo for vertical outlet and under base kit h100 mm
KACL.1050	
KACL.1064#BF	

falmec

8034122369778

PF		
S	Falmec Lab	
M		
AEC	41.50	kWh/a
EEC	A	
FDE	34.60	
FDEC	A	
LE	15.40	
LEC	D	
GFE	65.1	
GFEC	D	
Qmin	224	m^3 /h
Qmax	450	m^3 /h
Qboost	605	m^3 /h
SPEmin	40	dBa
SPEmax	57	dBa
SPEboost	67	dBa
PO		
PS	0.28	W
PI		
F	0.80	
EEI	54.00	
Qbep	364	m^3 /h
Pbep	315	Pa
Qboost	605	m^3 /h
Wbep	92	W
WL	20.00	W
Emiddle	309	lux
Lwa-SPEmax	57	dBa

PF_Scheda prodotto conforme a 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m^3/h) at min speed in normal use / Qmax_Air flow (in m^3/h) at max speed in normal use / Qboost_Air flow (in m^3/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airbone acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / P0_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps).
PI_Additional information according to 66/2014 Calculation methods: EN 61591:2020 F_Time increase factor / EEI_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximun air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.